

CTC-1052L 4G Medical Alarm with Voice Prompt

Even better than before, the newly improved CTC-1052L 4G Medical Alarm System now comes with a user-friendly voice prompt feature for learn-in sensor instructions, emergency events, and power/inactivity status. The step-by-step instructional voice prompt further simplifies the sensor learning procedure, making learning in a new emergency pendant quick and easy!

The CTC-1052L is incredibly easy to integrate into users' daily lives. Its advanced, crystal clear, echo-cancelling two-way voice communication allows the Monitoring Center to listen in and talk to the user to better assess the situation and dispatch help immediately if needed. CTC-1052L is specially designed with multiple alarm reporting and communication protocols, adding its versatility for the most advanced telecare monitoring market. CTC-1052L utilizes Climax's advanced F1 technologies to increase signal transmission speed, and further extend communication range, up to 2000ft. CTC-1052L gives users and their loved ones the assurance that help is just a call and a button push away.



- **Voice Prompt: Learn-in Sensor Setup, Emergency Events & Status**
- **Front Test button for easy access**
- **Long Communication Range, up to 2000ft**
- **Alarm Reporting over 4G**



4G Medical Alarm CTC-1052L

Features

- 4G Medical Alarm Panel
- Voice Prompts: Learn-in Sensor instructions, Emergency events, Power/Inactivity timer status
- Alarm Reporting Protocol Options: Contact ID / Contact ID data*, SMS, or Speech
- Two-Way Hands-Free Voice Communication
- Large, red Help button for easy access
- Integrate multiple devices/sensors: Wrist Transmitter, Emergency Pendant, Fall Sensor, PIR Motion Sensor, Panic Button, Smoke Detector, Water Leakage Sensor, and CO2 Sensors...etc.
- Test button on front of panel for easy access to trigger Test Report and reset Mobility Check Time
- Long Communication Range
- Programming Options: Local, Remote (SMS Programming)
- Powerful 3W Speaker
- Silent Emergency Call
- Supervision for Emergency Pendants
- Mobility Check, Automatic Check-in report, "Help Arrived" Confirmation, Fault Reporting
- Battery backup in case of power failure
- Certification Compliance: UL1635 & 1637, CSA C22.2 No. 205, PTCRB, CE, FCC

*Note: Contact ID data protocol might require Climax converter, please contact sales representative for detailed information.

Specifications

Frequency	F1 919MHz / 433MHz
Power Source	12V@1A Power Adaptor
Backup Battery	7.2V, 1100mAh Ni-MH Rechargeable Battery Pack
Battery Life	20hrs**
Range	2000ft
Operating Temperature	-10°C to 45°C (14°F to 113°F)
Operating Humidity	Up to 85% non-condensing
Dimensions	200mm x 150mm x 55mm

**Note: Actual battery life varies with settings, conditions, operating environment, and usage.