

## Battery Operated GSM & Voice Dialer CTC-763G

Upgrade your existing local home alarm panels with this dialer. CTC-763G allows up to 6 phone numbers for voice reporting, and up to 2 SMS numbers for text messages. It also features a two-way hands-free voice communication for the recipient to follow up the alarm report.

CTC-763G allows you to deal with the situation and respond without any delay. Thus delivers further protection for you, your loved ones, your properties, and ensuring a peace of mind.



### Features:

- Battery operated with life expectancy of >2 years in a typical domestic environment
- Compatible with CTC-902 & CTC-1110 Alarm Control Panels
- Choice of voice reporting and/or SMS message
- Up to 6 different phone numbers can be stored in priority order, or in 3 categories for Burglar/Panic/Technical, Fire/Gas, and Medical
- 2 independent numbers for SMS reporting
- SMS editing: 14 characters x 2 lines = 32 characters in total
- A 16 x 2 characters backlit full text LCD display
- A 16-button backlit keypad facilitate smooth user friendly operation
- 4 specific Alarm Messages of **Burglar, Fire, Panic, and Medical**, and a common Address Message can be recorded
- Call-Acknowledgement by the recipient ensures the calls are well-received
- **“Two-Way Hands-Free Voice Communication”** allows the call recipient to talk with you and listen to what’s happening on your side through the built-in microphone & speaker
- Built-in Transmitter to silence the siren during Two-Way Communication
- Capable of using power adaptor as an option
- One Auxiliary Input for the connection of wired contact (Normal Open / Normal Close)

## Specifications:

- Power: Alkaline D cell x 4 or 12V 1A switching power
- Battery time: 2 years or over
- Frequency: 433 MHz / 868.35 MHz / 868.6375 MHz FM
- Range: 433 MHz or 868.35 MHz: Over 200 meters in open space  
868.6375 MHz: Over 300 meters in open space
- Operating temperature: -10° to +45°C
- Humidity: up to 85% non-condensing
- Dimensions: 239.50 x 168 x 44 mm



Climax Technology Co., Ltd.  
Website: <http://www.climax.com.tw>  
Email: [sales@climax.com.tw](mailto:sales@climax.com.tw)