

20-Zone PSTN Voice & Digital Communicating Panel CTC-1141 Plus

- **Small in size!**
- **Big in features!**
- **Installed in minutes!**



A Modern, Effective and Versatile 20-zone Household Security System for the world's Monitoring System alarm market is heralded by our CTC-1141 Plus.

It is packed with simple PLUG & PLAY functionality, with the design for easy installation and easily self-taught.

Smart, sophisticated and safeguarded, CTC-1141 Plus certainly brings the most advanced Wireless Alarm System for you and your loved ones.

- ✓ **PLUG & PLAY**
- ✓ **REMOTE SYSTEM CONTROL**
- ✓ **SELF-TAUGHT, SMART FEATURES**
- ✓ **FAULT-PROOF SUPERVISION**
- ✓ **TEXT ZONE NAMING**

Features:

- A 20-zone full-feature Wireless Control Panel with built-in Voice & Digital dialers
- Total 6 numbers for Voice & Digital Reporting
- Communication protocol: Contact ID
- Voice messages can be recorded (max. of 20 sec) for voice reporting
- Remote arming & disarming via DTMF commands
- Remote uploading and downloading assist the Central Stations with processing and management of the data collected from the system.
- A 16 x 2 characters backlit full text LCD display
- Each of the 20 zones can be individually named/edited by the user for quick recognition of designated areas
- Built-in Transmitter to activate Outdoor Bell Box or Wireless Siren.

- **“Home”** arming option offers full protection while you are home, yet allows you to move freely inside without triggering the alarm
- Full Supervision to ensure the problem-free operation of the system.
- Door Open Closed Monitoring before system arming adds extra caution.
- Fault Detection and Display
- Tamper detection protects the unit from unauthorized opening or removal from its mounting surface
- The Panel can interface with the following:
 - RFID Tag Reader, Passive Infrared detector, Pet Immune Passive Infrared detector, Door Contact, Remote Keypad, Remote Controller, Wrist Emergency Transmitter, Optical Smoke Detector, Carbon Monoxide Detector, Water Sensor, Night Switch, Fixed Panic Button, External Bell Box, Wireless Siren, Universal Receiver and Repeater.

Specifications:

- Power: 9V 500mA adaptor
- Back up battery: 7.2V 600 mAh Ni-mh rechargeable battery x 6
- Battery back-up time: 8 hours minimum
- Alarm output: 104dB @ 1M
- Frequency available: 433 MHz / 868.35 MHz / 868.6375 MHz FM
- Range: 433 MHz or 868.35 MHz: Over 200 meters in open space
868.6375 MHz: Over 300 meters in open space
- Operating temperature: -10° to +45°C
- Humidity: up to 90% non-condensing
- Dimensions: 185 X 120 X 26 mm
- Complied with FCC & CE certification requirement



Climax Technology Co., Ltd.
 Website: <http://www.climax.com.tw>
 Email: sales@climax.com.tw