

Battery Operated Centrally Monitored GSM & SMS Communicating Control Panel CTC-1545GS

This professional and sophisticated battery-operated system makes a clean break from ever worrying about unexpected total power failure, and offers you the convenience of **mounting it wherever you like without the hassle of wiring to a wall outlet or phone line.**



This 20-zone control panel offers extreme convenience, reliability and flexibility of alarm reporting to Central Monitoring Station numbers as well as send a SMS text messaging to your Mobile phone in emergencies. Even if there is no PSTN lines available, simply insert a GSM SIM card and you can enjoy it full protection at anywhere, anytime.

Features:

- Completely wire and tangle free! Battery-operated and can be installed wherever with GSM reception, offering a flexible and easy installation
- Great solution for vacant premises, summer resorts, cruise/house boats...etc.
- Alarm Reporting: Contact ID, SMS Text Message to Central Monitoring Station, and/or, SMS Text Message to user's mobile phone
- Dual language available upon request
- Battery operated with life expectancy of >2 years in a typical domestic environment, optional DC power & Terminal
- A 20-zone full featured Stand-alone Wireless Control Panel
- Telephone numbers : 2, either of the Central Monitoring Station or Mobile phone numbers
- Remote command and access to the System from anywhere via SMS
- Multiple User Codes (including Temporary and Cleaner code) ensure the ultimate security in today's life style
- **"Day Home" & "Night Home"** arming option offers full protection while you are home, yet allows you to move freely inside without triggering the alarm

- Full **Supervision** to ensure the problem-free operation of the system (only available on 868MHZ panel)
- “**Two-Way Voice Communication**” allows the call recipient to talk with you and listen to what’s happening on your side through the built-in microphone & speaker
- Each of the 20 zone can be individually named/edited by the user for quick recognition of designated areas
- 20 time-stamped event logs
- A 16 x 2 characters backlit full text LCD display
- A 16-button backlit keypad facilitate smooth user friendly operation
- Capable of using power adaptor as an option

Specifications:

- Power: Alkaline D cell x 4 or 12V 1A switching power
- Battery time: 2 years or over
- Frequency: 433 MHz / 868.35 MHz / 868.6375 MHz FM
- Range: 433 MHz or 868.35 MHz: Over 200 meters in open space
868.6375 MHz: Over 300 meters in open space
- Operating temperature: -10° to +45°C
- Humidity: up to 85% non-condensing
- Dimensions: 239.50 x 168 x 44 mm



Climax Technology Co., Ltd.
Website: <http://www.climax.com.tw>
Email: sales@climax.com.tw