

IP & PSTN Based Centrally Monitored Alarm Box CTC-1735

The CTC-1735 IP Box represents a brand new breakthrough from traditional centrally monitored alarm panels. The flexible range of products encompasses a selection of multi-path communications to Alarm Receiving Centres to suit your application and budget, including PSTN and TCP/IP over Internet.

Putting *fashion* into security, CTC-1735 not only offers the most elegant & smallest design for Alarm Panels, but also brings the concept of **Zero-Touch Installation** to live that allows easy operation every time.

Also compatible with our CTC-1807 IP Camera, that fulfills the dream of offering a **Total IP Solution** which provides 24-hour instant surveillance & pre- & post- alarm image capture.

This range of innovative features heralds the vanguard of a cost-effective and highly integrated security system that provides enhanced protection for you, your loved ones and your property.

**Small in size, Big in Features
& Zero Touch Installation!**



Features:

- A 20-zone full-featured Wireless IP Panel with built-in **Web Page**
- 30 time-stamped event logs
- “**Full Arm, Home Arm**” arming option available
- **UPnP** basic device
- Automatic configuration for Router setting that offers easier access to Web GUI from external site (by UPnP protocol)
- **Polling function** included as Port forwarding back-up
- Capable of remote Program, Access, and Control via **Internet Browser (CGI scripts)** or **M2M Polling (XML scripts)**
- Capable of remote Upgrading via internet connection

- IP Address: DHCP or Static IP programmable
- Add up to 8 wired / wireless **IP cameras** (more cameras adding available upon request)
- IP Camera image captured by triggering the IP Alarm System; with pre-5 secs & post-5 secs of images at about 3 frames per second
- Simplified DDNS setup
- Each zone can be individually named/edited (with a max. of 10 characters) for quick recognition of designated area
- Full Supervision to ensure the problem-free operation of the system
- Interference detection is available at user's discretion to report signal jamming

Specifications:

- Power Supply: 12V 1A switching power (12V 1.5A switching power for Wi-Fi version)
- Back up battery: 600 mAh Ni-mh rechargeable battery x 6
(780 mAh Ni-mh rechargeable battery x 6 for Wi-Fi version)
- Battery Back-up time: 6 hours minimum
- Alarm Output: 100db @ 1M
- Frequency available: 433MHZ / 868.35MHZ / 868.6375MHz
- Range: 433MHZ or 868.35MHZ: over 200 meters in open space
868.6375MHZ: over 300 meters in open space
- Temperature Range: -10° to +45°C
- Humidity: up to 90% non-condensing
- Dimensions: 135 X 169 X 27 mm



Climax Technology Co., Ltd.
 Website: <http://www.climax.com.tw>
 Email: sales@climax.com.tw