

CTC-902 Battery Operated, 20 Zone Control Panel

This professional and sophisticated battery operated system makes a clean break from ever worrying about unexpected total power failure and offers you the convenience of mounting it wherever you pleased without the hassle of wiring to a wall outlet. This year-round hi-tech protection is what you, your love ones, and your investment deserve.



FEATURES:

- Battery operated with life expectancy of 2.5 years in a typical domestic environment
- A 20-zone full featured Stand-alone Wireless Control Panel.
- A 16 x 2 characters backlit full text LCD display
- A 16-button backlit keypad facilitate smooth user friendly operation
- Each of the 20 zones can be individually named/edited by the user for quick recognition of designated areas
- Multiple User Codes (including Temporary and Cleaner code) ensure the ultimate security in today's life style
- 20 time-stamped event logs
- Each zone can be programmed individually into different zone types with device attributes
- Built-in Transmitter to activate Outdoor Bell Box or Wireless Siren.
- "Home" arming option offers full protection while you are home, yet allows you to move freely inside without triggering the alarm
- Tamper detection protects the unit from unauthorised opening or removal from it's mounting surface
- Full Supervision to ensure the problem-free operation of the system (only available on 868MHZ panel)
- Compatible with voice dialler, CTC-729, for voice reporting
- Compatible with digital dialler, CTC-742, for digital reporting.

SPECIFICATION:

- Battery: Alkaline D cell x 4
- Alarm Output: 104db @ 1M
- Frequency available: 433MHZ / 868.35MHZ / 868.6375MHz
- Range: 433MHZ or 868.35MHZ: Over 200 meters in open space
868.6375MHZ: Over 300 meters in open space
- Temperature Range : -10°C ~ +45°C
- Humidity: Up to 90% non condensing
- Complied with FCC & CE certification requirement.



Climax Technology Co., Ltd.

Website: <http://www.climax.com.tw>

Email: sales@climax.com.tw