

Compact Voice Communicating PSTN Panel CTC-1131

- **Small in size!**
- **Big in features!**
- **Installed in minutes!**

A Modern, Effective and Versatile 20-zone Household Security System for the world's DIY alarm market is heralded by our CTC-1131.



It is packed with simple PLUG & PLAY functionality, with the design for easy installation and easily self-taught.

Smart, sophisticated and safeguarded, CTC-1131 certainly brings the most advanced Wireless Alarm System for you and your loved ones.

- | | |
|-------------------------------|---------------------------|
| ✓ PLUG & PLAY | ✓ REMOTE SYSTEM CONTROL |
| ✓ SELF-TAUGHT, SMART FEATURES | ✓ FAULT-PROOF SUPERVISION |
| ✓ TEXT ZONE NAMING | |

Features:

- A 20-zone full featured Wireless Control Panel with built-in Voice dialler. Each of the 20 zones can be individually named/edited by the user for quick recognition of designated areas
- Up to 6 different phone numbers can be pre-stored in the system and dialled to summon help in priority order
- Remote arming & disarming via DTMF commands
- 1 recordable common Address message with a capacity of 10 seconds
- 4 fixed Alarm voice messages for Burglar, Emergency, Fire & Medical alarms
- Call-Acknowledgement by the recipient ensures the calls are well-received
- **“Listen-In”** feature allows the call recipient to listen in to what is happening on your side
- A 16 x 2 characters backlit full text LCD display
- Remote command and access to the System from anywhere via a telephone line
- Built-in Transmitter to activate Outdoor Bell Box or Wireless Siren.
- **“Home”** arming option offers full protection while you are home, yet allows you to move freely inside without triggering the alarm
- Full Supervision to ensure the problem-free operation of the system

- Door Open Closed Monitoring before system arming adds extra caution.
- Fault Detection and Display
- Tamper detection protects the unit from unauthorised opening or removal from it's mounting surface
- Compatible with our Home Automation Power Switch, which can also be remotely controlled via a telephone line
- The Panel can interface with the following:
 - ◆ RFID Tag Reader, Passive Infrared detector, Pet Immune Passive Infrared detector, External Pet Immune Passive Infrared detector, Door Contact, Remote Keypad, Remote Controller, (Wrist Emergency Transmitter, Optical Smoke Detector, Carbon Monoxide Detector, Water Sensor, Night Switch, Fixed Panic Button, Power Switch, External Bell Box, Wireless Siren, Universal Receiver and Repeater

Specifications:

- Power: 9V 500mA adaptor
- Back up battery: 7.2V 600 mAh Ni-Mh rechargeable battery x 6
- Battery back up time: 8 hours minimum
- Alarm Output: 104db @ 1M
- Frequency available: 433 MHz / 868.35 MHz / 868.6375 MHz
- Range: 433 MHz or 868.35MHz: Over 200 meters in open space
868.6375MHz: Over 300 meters in open space
- Operating temperature: -10° to +45°C
- Humidity: Up to 90% non-condensing
- Dimensions: 185 x 120 x 26 mm
- Complied with FCC & CE certification requirement



Climax Technology Co., Ltd.

Website: <http://www.climax.com.tw>

Email: sales@climax.com.tw