

Battery Operated GSM & Voice Communicating 20-Zone Control Panel CTC-1563

This professional and sophisticated battery-operated system makes a clean break from ever worrying about unexpected total power failure, and offers you the convenience of **mounting it wherever you like without the hassle of wiring to a wall outlet or phone line.**



It allows up to 6 phone numbers for voice reporting, and up to 2 SMS numbers for text messages. CTC-1563 allows you to deal with the situation and respond without any delay. Thus delivers further protection for you, your loved ones, your properties, and ensuring a peace of mind.

Features:

- Completely wire and tangle free! Battery-operated and can be installed wherever with GSM reception, offering a flexible and easy installation
- Great solution for vacant premises, summer resorts, cruise/house boats...etc.
- Dual language available upon request
- Battery operated with life expectancy of >2 years in a typical domestic environment, optional DC power & Terminal
- A 20-zone full featured Stand-alone Wireless Control Panel
- Choice of voice reporting and/or SMS message
- 2 independent numbers for SMS reporting
- Up to 6 different phone numbers can be stored in priority order, or in 3 categories for Burglar/Panic/Technical, Fire/Gas, and Medical
- Each of the 20 zone can be individually named/edited by the user for quick recognition of designated areas
- Multiple User Codes (including Temporary and Cleaner code) ensure the ultimate security in today's life style

- “**Day Home**” & “**Night Home**” arming option offers full protection while you are home, yet allows you to move freely inside without triggering the alarm
- 20 time-stamped event logs
- A 16 x 2 characters backlit full text LCD display
- A 16-button backlit keypad facilitate smooth user friendly operation
- 4 specific Alarm Messages of **Burglar, Fire, Panic, and Medical**, and a common Address Message can be recorded
- Call-Acknowledgement by the recipient ensures the calls are well-received
- “**Two-Way Hands-Free Voice Communication**” allows the call recipient to talk with you and listen to what’s happening on your side through the built-in microphone & speaker
- Full Supervision to ensure the problem-free operation of the system (only available on 868MHZ panel)
- Capable of using power adaptor as an option

Specifications:

- Power: Alkaline D cell x 4 or 12V 1A switching power
- Battery time: 2 years or over
- Frequency: 433 MHz / 868.35 MHz / 868.6375 MHz FM
- Range: 433 MHz or 868.35 MHz: Over 200 meters in open space
868.6375 MHz: Over 300 meters in open space
- Operating temperature: -10° to +45°C
- Humidity: up to 85% non-condensing
- Dimensions: 239.50 x 168 x 44 mm



Climax Technology Co., Ltd.
Website: <http://www.climax.com.tw>
Email: sales@climax.com.tw