

# DC-15C2 Door Contact

An Ideal Choice to Guard Your Door and Window



- Extension Terminal to Connect to Roller Shutter / Wired Detector
- Long Battery Life
- Serves as a Universal Transmitter

DC-15C2 is a wireless Door / Window Contact designed to monitor the opening and closing of doors and windows. DC-15C2 is multi-functional, with a built-in extension terminal which allows roller shutter or an existing wired sensor to be connected, and also serves as a universal transmitter. When connected to roller shutter, DC-15C2 will report to the control panel when the shutter is raised to certain level.

DC-15C2 has a compact and low-profile design allowing it to seamlessly fit into any home décor, and ideal for both residential and commercial installations and usage. DC-15C2 adopts the latest RF technologies to deliver long RF range, fast signal transmissions, and long battery life.

DC-15C2 alerts the system control unit to any irregular activities and sends low battery signals as well as supervision signals to check system integrity, for peace of mind and a safer home.

## Features

- Monitors the opening and closing of doors, windows, cabinets and drawers
- Built-in extension terminal for enhanced flexibility to add roller shutter or wired detectors
- Doubles as a universal transmitter
- Randomized Supervision signals to check system integrity
- Wireless for easy installation
- Extensive RF communication range & faster signal transmission
- Tamper protection
- Low battery detection
- LED serves as a fault and test mode indicator

## Specifications

### DC-15C2-F1

Frequency	868 MHz / 433 MHz
Power Source	3V, CR2 Lithium battery x 1
Battery Life	6.6 years*
Operating Temperature	-10°C to 45°C (14°F to 113°F)
Operating Humidity	Up to 85% non-condensing
Dimensions	107 mm x 32 mm x 22 mm

\* Note: Actual battery life may vary with product settings, operating environment, and usage patterns.