

DCSV-29 Door Contact / Shock Sensor

Double the Protection in One Device



DCSV-29 is a door / window contact with built-in shock sensor. It combines two functions in one unit to bolster perimeter protection while featuring more extensive RF range and faster signal transmission.

Mounted on door or window frames, DCSV-29 monitors the opening and closure of doors or windows and detects the impact caused by shock events.

The early detection provided by DCSV-29 effectively discovers and deters a break-in attempt before a door or window is opened, thereby minimizing damage caused by burglary or attack.

With three levels of adjustable sensitivity, each installation can be fine-tuned to ensure reliable coverage without false alarms. DCSV-29 also has a tamper switch for sabotage detection.

DCSV-29's elegant and modern design allows it to fit seamlessly into any home decor, ideal for both residential / commercial installation and usage.

Features

- Door/window opening or window glass break & shock detection
- Three adjustable sensitivity threshold levels (high, medium and low)
- Tamper switches for sabotage detection
- Enable security and home automation systems scheduling, scene creation to turn on / off appliances accordingly
- Remote settings of material and sensitivity
- Works on wood, glass, metal and concrete
- Extensive RF range, faster signal transmission
- Wireless for easy installation
- Supervisory signals ensure proper operation

Specifications

DCSV-29-F1

Frequency	868 MHz / 433 MHz
Power Source	3V CR123 battery x 1
Battery Life	5 years*
Operating Temperature	-10°C to 45°C (14°F to 113°F)
Operating Humidity	Up to 85% non-condensing
Dimensions	93.5 mm x 31 mm x 22.5 mm

* Note: Battery life varies by configuration mode, usage, and environment.